



**D5719-1 RADIUS BLOCK**

**NOTES:**

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET, 0.063 THICK  
PER QQ-A-250/11 OR AMS-QQ-A-250/11  
OR AMS 4025 OR AMS 4027 OR ASTM B209  
REF DART SPEC M6061T6S  
OR: 6061-T6/T651/T6510/T6511/T62 ALUMINUM BAR  
PER QQ-A-225/8 OR AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116) OR  
QQ-A-200/8 OR AMS-QQ-A-200/8 (OR AMS 4160) OR ASTM B211 OR ASTM B221  
REF DART SPEC M6061T6B
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER DART QSI 044 6.7
- 7) WEIGHT: 0.01 lbs

RELEASED  
2019-09-27

APPROVED

A	NEW ISSUE	RF	19.07.19
REV.	DESCRIPTION	BY	DATE
DESIGN	RF	DART AEROSPACE USA, INC.	
DRAWN	RF	HILLSBORO, OR	
CHECKED	PM	DRAWING NO.	REV. A
MFG. APPR.	DD	D5719	SHEET 1 OF 1
APPROVED	VS	TITLE	SCALE
DE APPR.	DS	RADIUS BLOCK	NTS
DATE	19.07.19	COPYRIGHT © 2019 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	